

		Spoke Type	Spoke Count		RRP £	Weight g	Spoke Length NDS / DS
700c	 6 Bolt	Front	J-BEND	24H	PRO 5 Front Standard 100mm	230	860 / 284 / 286
					PRO 5 Front Boost 110mm	230	870 / 284 / 286
			32H	PRO 5 Front Standard 100mm	230	286 / 288	
			PRO 5 Front Boost 110mm	230	286 / 288		
		Rear	J-BEND	24H	PRO 5 Rear Standard 135mm	350	985 / 286 / 284
					PRO 5 Rear Boost 148mm	350	990 / 286 / 284
	32H		PRO 5 Rear Standard 135mm	350	289 / 286		
		PRO 5 Rear Boost 148mm	350	289 / 286			
	 Centrelock	Front	J-BEND	24H	PRO 5 CL Front Standard 100mm	230	820 / 286 / 288
					PRO 5 CL Front Boost 110mm	230	825 / 286 / 288
			32H	PRO 5 CL Front Standard 100mm	230	290 / 291	
				PRO 5 CL Front Boost 110mm	230	290 / 292	
			STRAIGHT PULL	24H	PRO 5 CL SP Front Standard 100mm	270	295 / 296
					PRO 5 CL SP Front Boost 110mm	270	296 / 296
		Rear	J-BEND	24H	PRO 5 CL Rear Standard 135mm	230	965 / 286 / 284
					PRO 5 CL Rear Boost 148mm	230	970 / 286 / 284
			32H	PRO 5 CL Rear Standard 135mm	230	1015 / 290 / 287	
				PRO 5 CL Rear Boost 148mm	230	1020 / 290 / 288	
STRAIGHT PULL			24H	PRO 5 CL SP Rear Standard 135mm	390	296 / 293	
				PRO 5 CL SP Rear Boost 148mm	390	296 / 293	

RIM ONLY

Rim DIA.	Part number	Description	RRP £	Weight g	ERD mm
700c	WHSP077	RX24 24H Black	125	495	596
	WHSP078	RX24 32H Black	125	495	596

- › High performance aluminium gravel wheelset, built for comfort and durability.
- › Recommended maximum system weight: 130kg.
- › RX24 Front Standard wheels come supplied with 12mm endcaps.
- › RX24 Rear Standard wheels come supplied with 142 x 12mm endcaps.
- › RX24 Rear Boost wheels come supplied with 148 x 12mm endcaps.

Hubs are available in seven anodised colours: Red, Orange, Blue, Purple, Silver, Black, Bronze.



 Recommended tyre width: 30mm – 64mm

