


ITEM No.	DRAWING No.	DESCRIPTION	QTY.
1	BB017-04	T47 86-92 Drive Side Cup - 24mm	1
2	BB017-05	T47 86-92 Non-drive Side Cup - 24mm	1
3	BB017-03	T47 Centre Tube	1
4	BBSP1085	BB Stainless Steel Bearing	2
5	BBSP104	BB Outer Seal	2
6	BB018-04	T47 Bottom Bracket Spacer - 2.5mm	1
7	OR36X1.5N	36 x 1.5mm O-Ring	2



## CAUTION: READ THIS BEFORE INSTALLING YOUR BOTTOM BRACKET!

Riding bicycles can be dangerous. These instructions should be read thoroughly before installation. Failure to follow these instructions before installing and using Hope Technology Components can result in severe injury or death.

### BOX CONTENTS

- 1 x Bottom bracket assembly (drive side cup and bearing, non-drive side cup and bearing and centre tube)
- 2 x Bearing Covers • 1 x 2.5mm Spacer

### TOOLS REQUIRED

- 30mm BB Tool (HTT00155) • 19mm Spanner
- Torque Wrench • Grease

### HOPE WARRANTY

All Hope Technology Components are covered for two years from original date of purchase against manufacturer defects in material and workmanship. Proof of purchase is required. Product must be returned to the original retailer to process any warranty claim. This warranty does not cover any damage caused through mis-use or failing to comply by the recommendations given in this manual. This warranty does not affect your statutory rights.

**HOPE TECHNOLOGY**  
(IPCO) Limited

Hope Mill, Calf Hall Road  
Barnoldswick, Lancashire  
BB18 5PX, United Kingdom

T: 01282 851400 E: info@hopetech.com W: hopetech.com

## PRELIMINARY CHECKS

**001** Measure your bottom bracket shell and crankset. Check compatibility using the table.

**002** It is critical to bearing life that the frame is prepared correctly. Chase threads and face ends of BB shell to ensure they are clean and square.

## INSTALL CUPS

**001** Determine spacers required (see compatibility chart).

**002** Apply grease to the BB cups and the frame BB shell. Thread Drive-Side BB cup with centre tube and appropriate spacers (if required) anti-clockwise into RH side of frame, by hand initially to ensure threads are not crossed. Using BB tool tighten to **35-40Nm**.

**003** Thread Non-Drive BB cup and appropriate spacers (if required) clockwise into LH side of frame and tighten to 35-40Nm.

**004** Locate bearing covers over external face of bearings. A smear of grease will help keep them in place.










## INSTALL CRANKS

Follow manufacturer's instructions. **NOTE:** Hope BB's allow cranks to fit directly in the bearing inner race, not through a plastic bush.

HOPETECH.COM



# BOTTOM BRACKET COMPATIBILITY

	BB SHELL TYPE	SPINDLE DIAMETER	BB SHELL WIDTH	FULLY ASSEMBLED OVER BEARING WIDTH	NON-DRIVE SPACER	DRIVE SPACER
1	 <p>T47 Thread</p>	24mm	 <p>86.5mm</p>	 <p>91mm</p>	None	None
2	 <p>T47 Thread</p>	24mm	 <p>89.5mm</p>	 <p>96.5mm</p>	None	1 x 2.5mm (BB018-04)
3	 <p>T47 Thread</p>	24mm	 <p>92mm</p>	 <p>96.5mm</p>	None	None