

			Spoke Type	Spoke Count		RRP £	Spoke Length NDS / DS
700c	 6 Bolt	Front	J-BEND	24H	PRO 5 Front Standard 100mm	200	283 / 285
					PRO 5 Front Boost 110mm	200	283 / 285
				32H	PRO 5 Front Standard 100mm	200	285 / 287
					PRO 5 Front Boost 110mm	200	285 / 287
		Rear	J-BEND	24H	PRO 5 Rear Standard 135mm	325	285 / 283
					PRO 5 Rear Boost 148mm	325	285 / 283
				32H	PRO 5 Rear Standard 135mm	325	288 / 285
					PRO 5 Rear Boost 148mm	325	288 / 285
	 Centrelock	Front	J-BEND	24H	PRO 5 Front Standard 100mm	200	285 / 287
					PRO 5 Front Boost 110mm	200	285 / 287
				32H	PRO 5 Front Standard 100mm	200	289 / 291
					PRO 5 Front Boost 110mm	200	289 / 291
		Rear	STRAIGHT PULL	24H	PRO 5 CL Front Standard 100mm	240	295 / 295
					PRO 5 CL Front Boost 110mm	240	295 / 295
			J-BEND	24H	PRO 5 CL Rear Standard 135mm	325	285 / 283
					PRO 5 CL Rear Boost 148mm	325	285 / 283
				32H	PRO 5 CL Rear Standard 135mm	325	289 / 287
					PRO 5 CL Rear Boost 148mm	325	289 / 287
			STRAIGHT PULL	24H	PRO 5 CL SP Rear Standard 135mm	365	295 / 292
					PRO 5 CL SP Rear Boost 148mm	365	295 / 292

RIM ONLY


Rim DIA.	Part number	Description	RRP £	ERD mm
700c	WHSP056	20.FIVE 24H Black	115	594
	WHSP057	20.FIVE 32H Black	115	594

- › All season aluminium road wheelset.
- › Recommended maximum system weight: 130kg.
- › 20.FIVE Front Standard wheels come supplied with 12mm endcaps.
- › 20.FIVE Rear Standard wheels come supplied with 142 x 12mm endcaps.
- › 20.FIVE Rear Boost wheels come supplied with 148 x 12mm endcaps.

Hubs are available in seven anodised colours: Red, Orange, Blue, Purple, Silver, Black, Smoke.



Recommended tyre width: 25mm – 56mm



20.FIVE